

VARSTEEL**STEEL H
PILES****SPEC A-36/44W/A572-50/A992**

| New Designation | | Depth In. | Flange | | Web Thickness In. | Section Modulus In. ³ |
|-------------------------------------------------------------|---------------|--------------|--------------|-------------------------|-------------------------|----------------------------------------|
| ASTM Imp. | CDN Metric | | Width In. | Thickness (mean) In. | | |
| HP8 x 36 | HP200 x 54 | 8.02 | 8.16 | .445 | .445 | 29.8 |
| HP10 x 42 x 57 | HP250 x 62 | 9.70 | 10.08 | .420 | .415 | 43.4 |
| | x 85 | 9.99 | 10.22 | .565 | .565 | 58.8 |
| HP12 x 53 x 63 x 74 x 84 x 89 x 102 x 117 | HP310 x 79 | 11.78 | 12.04 | .435 | .435 | 66.8 |
| | x 94 | 11.94 | 12.13 | .515 | .515 | 79.1 |
| | x 110 | 12.13 | 12.22 | .610 | .605 | 93.8 |
| | x 125 | 12.28 | 12.28 | .685 | .685 | 106 |
| | x 132 | 12.35 | 12.33 | .720 | .720 | 111 |
| | x 152 | 12.55 | 12.62 | .820 | .820 | 129 |
| HP13 x 60 x 73 x 87 x 100 | HP330 x 89 | 12.56 | 12.91 | .461 | .461 | 80.6 |
| | x 109 | 12.76 | 12.99 | .567 | .567 | 98.9 |
| | x 129 | 12.95 | 13.11 | .665 | .665 | 117 |
| | x 149 | 13.15 | 13.19 | .764 | .764 | 134 |
| HP14 x 73 x 89 x 102 x 117 | HP360 x 108 | 13.61 | 14.58 | .505 | .505 | 107 |
| | x 132 | 13.83 | 14.70 | .615 | .615 | 131 |
| | x 152 | 14.01 | 14.78 | .705 | .705 | 150 |
| | x 174 | 14.21 | 14.88 | .805 | .805 | 172 |